



Wabco EaseTec M8

SECTION 1: Identification

Product identifier

Trade name

Wabco EaseTec M8

Article No.

8999400014

Recommended use of the chemical and restrictions on use

Product type

Mixture

Use

Lubricating grease

Not suitable for use in

Any other purpose. Not intended for human consumption.

Supplier's details

SDS created by

Global Division B Product Compliance Mgmt. System (BWC)

Supplier

ZF CV Systems North America LLC

Address

1220 Pacific Drive

Auburn Hills

48326 MI

USA

Telephone

+1 248-270-9300

Email

msds.zf-aftermarket@zf.com

Contact person

Global Division B Product Compliance Mgmt. System (BWC)

Email address

msds.zf-aftermarket@zf.com

Emergency phone number

(+49) 89 19 240



Wabco EaseTec M8

Available outside office hours

Yes

SECTION 2: Hazard identification

Classification of the substance or mixture and any national or regional information

Classification according to Globally Harmonized System (GHS)

Classification

Eye irritation, hazard category 2

Reproductive toxicity, hazard category 2

Hazard statements

H319, H361

Label elements, including precautionary statements

Labelling according to Globally Harmonized System (GHS)

Hazard pictograms



Signal word

Warning

Hazard statements

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container to an approved waste disposal facility in accordance with all local, regional, national and international regulations..

Other hazards which do not result in classification

No data available.



SAFETY DATA SHEET
According to Globally Harmonized System
(GHS)

Version number: 1
Issued: 2026-08-03

Wabco EaseTec M8

SECTION 3: Composition/information on ingredients

Mixture

Chemical name	CAS No. EC No. REACH No. Index No.	Concentration	Classification	H-phrase M factor acute M factor chronic	Specific concentration limits ATE	Note
Residual oils (petroleum), solvent-refined	64742-01-4 265-101-6 - -	15 - 40%	-	- - -		-
calcium carbonate	471-34-1 207-439-9 - -	10 - 30%	-	- - -		-
Molybdenum disulphide	1317-33-5 215-263-9 - -	7 - 13%	-	- - -		-
Solvent dewaxing heavy stone wax fraction	64742-65-0 265-169-7 - -	7 - 13%	-	- - -		-
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7 265-174-4 - -	5 - 10%	-	- - -		-
Propane-1,2-diol	57-55-6 200-338-0 - -	0.5 - 1.5%	-	- - -		-
Calcium dodecylbenzenesulphonate	26264-06-2 247-557-8 - -	0.5 - 1.5%	Acute Tox. 4 - oral, Skin Irrit. 2, Eye Dam. 1	H302, H315, H318 - -		-
Calcium dihydroxide	1305-62-0 215-137-3 - -	0.5 - 1.5%	Skin Irrit. 2, Eye Dam. 1, STOT SE 3 - resp. tract irrit.	H315, H318, H335 - -		-
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1 270-128-1 01-2119491299-23 -	0.1 - 1%	Repr. 2, Aquatic Chronic 3	H361f, H412 - -		-



Wabco EaseTec M8

Product based on

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.
Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SECTION 4: First-aid measures

Description of necessary first-aid measures

Get medical attention. If medical advice is needed, have product container or label at hand. Use personal protective equipment as required. Remove contaminated clothing and wash it before reuse. Wash skin surfaces thoroughly after contact.

Inhalation

Move affected person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention.

Skin contact

Brush off loose particles from skin. Wash with plenty of soap and water. Remove contaminated clothing and wash it before reuse. Get medical attention if symptoms occur.

Eye contact

Flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Remove contact lenses, if present and easy to do. Get medical attention if symptoms occur.

Ingestion

Ingestion may cause gastrointestinal irritation and diarrhea. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed

Inhalation

Not expected under normal use.

Skin contact

Not expected under normal use.

Eye contact

Pain or irritation, redness, watering.

Ingestion

Not expected under normal use.



SAFETY DATA SHEET

According to Globally Harmonized System
(GHS)

Version number: 1

Issued: 2026-08-03

Wabco EaseTec M8

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Use personal protective equipment as required.

SECTION 5: Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media

Use an extinguishing agent suitable for the surrounding fire. Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from the chemical (e.g. nature of any hazardous combustion products).

No specific fire or explosion hazard.

Hazardous thermal decomposition products: In a fire, hazardous decomposition products may be produced. carbon oxides (CO, CO₂) nitrogen oxides sulfur oxides metal oxide/oxides.

Special protective actions for fire-fighters

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special protective actions for fire-fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Put on appropriate personal protective equipment (see Section 8). Keep unnecessary personnel away. Avoid breathing vapor or mist. Provide adequate ventilation.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". Evacuate area.



SAFETY DATA SHEET

According to Globally Harmonized System
(GHS)

Version number: 1

Issued: 2026-08-03

Wabco EaseTec M8

Environmental precautions

Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Do not allow any potentially contaminated water, including rain water, runoff from fire fighting or spills, to enter any waterway, sewer or drain.

Methods and materials for containment and cleaning up

Small spill: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Absorb with an inert material and place in an appropriate waste disposal container. Place spilled material in a designated, labeled waste container. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Do not dry sweep. Avoid dust generation. Dispose of via a licensed waste disposal contractor.

Large spill: Stop leak if without risk. Move containers from spill area. For large spills, dike spilled material or otherwise contain it to ensure runoff does not reach a waterway. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

Reference to other sections

No data available

SECTION 7: Handling and storage

Precautions for safe handling

Preventive handling precautions

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not breathe dust. Do not ingest.

General hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Storage temperature : Store between the following temperatures: 4 to 40°C (39.2 to 104°F).

Shelf life : 3 years.

Specific end use(s)

No data available



Wabco EaseTec M8

SECTION 8: Exposure controls/personal protection

Control parameters

Exposure limits

See below OEL table.

National occupational exposure limits

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m ³ / F/cm ³	Source	Remark	Year
Residual oils (petroleum,) solvent-refined	- -	- / 5 / -	CA Alberta Provincial (Canada, 3/2023) [Oil]	OEL 8 hours: Form: Mist.	2023
Residual oils (petroleum,) solvent-refined	- -	- / 10 / -	CA Alberta Provincial (Canada, 3/2023) [Oil]	OEL 15 minutes: Form: Mist.	2023
Residual oils (petroleum,) solvent-refined	- -	- / 5 / -	CA Ontario Provincial (Canada, 6/2019) [Mineral oil, excluding metal working fluids (pure, highly and severely refined)]	TWA 8 hours: Form: Inhalable particulate matter	2019
calcium carbonate	- -	- / 10 / -	CA Alberta Provincial (Canada, 3/2023) [Calcium carbonate]	OEL 8 hours	2023
calcium carbonate	- -	- / 10 / -	CA Quebec Provincial (Canada, 2/2024) [Calcium carbonate]	TWAEV 8 hours: Form: total particulate matter	2024
molybdenum disulphide	- -	- / 3 / -	CA Alberta Provincial (Canada, 3/2023) [Molybdenum]	OEL 8 hours: (as Mo). Form: Respirable	2023



SAFETY DATA SHEET
According to Globally Harmonized System
(GHS)

Version number: 1
Issued: 2026-08-03

Wabco EaseTec M8

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m³ / F/cm³	Source	Remark	Year
			Metal and insoluble com- pounds]		
molybdenum disulphide	- -	- / 10 / -	CA Alberta Pro- vincial (Canada, 3/2023) [Molybdenum Metal and insoluble com- pounds]	OEL 8 hours: (as Mo).	2023
molybdenum disulphide	- -	- / 3 / -	CA British Columbia Pro- vincial (Canada, 9/2024) [molybdenum - metal and insoluble com- pounds]	TWA 8 hours: (as Mo). Form: Respirable	2024
molybdenum disulphide	- -	- / 10 / -	CA British Columbia Pro- vincial (Canada, 9/2024) [molybdenum - metal and insoluble com- pounds]	TWA 8 hours: (as Mo). Form: Inhalable.	2024
molybdenum disulphide	- -	- / 3 / -	CA Ontario Pro- vincial (Canada, 6/2019) [Molybdenum, metal and insoluble com- pounds]	TWA 8 hours: (as Mo). Form: Respirable par- ticulate matter	2019
molybdenum disulphide	- -	- / 10 / -	CA Ontario Pro- vincial (Canada, 6/2019) [Molybdenum, metal and	TWA 8 hours:(as Mo). Form: Inhalable partic- ulate matter	2019



Wabco EaseTec M8

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m³ / F/cm³	Source	Remark	Year
			insoluble com pounds]		
molybdenum disulphide	- -	- / 10 / -	CA Quebec Provincial (Canada, 2/2024) [molybdenum - metal [7439- 98-7] and insoluble com- pounds]		2024
molybdenum disulphide	- -	- / 3 / -	CA Quebec Provincial (Canada, 2/2024) [molybdenum - metal [7439- 98-7] and insoluble com- pounds]	TWAEV 8 hours: (as Mo). Form: respirable aerosol fraction	2024
molybdenum disulphide	- -	- / 20 / -	CA Saskat- chewan Provin- cial (Canada, 4/2021) [Molybdenum, metal and insoluble com- pounds]	STEL 15 minutes: (measured as Mo). Form: Inhalable frac- tion	2021
molybdenum disulphide	- -	- / 6 / -	CA Saskat- chewan Provin- cial (Canada, 4/2021) [Molybdenum, metal and insoluble com- pounds]	STEL 15 minutes: (measured as Mo). Form: respirable frac- tion.	2021
molybdenum disulphide	- -	- / 10 / -	CA Saskat- chewan Provin- cial (Canada, 4/2021) [Molybdenum, metal and insoluble com-	TWA 8 hours: (meas- ured as Mo). Form: Inhalable fraction	2021



SAFETY DATA SHEET
According to Globally Harmonized System
(GHS)

Version number: 1
Issued: 2026-08-03

Wabco EaseTec M8

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m ³ / F/cm ³	Source	Remark	Year
			pounds]		
molybdenum disulphide	- -	- / 3 / -	CA Saskat- chewan Provin- cial (Canada, 4/2021) [Molybdenum, metal and insoluble com- pounds]	TWA 8 hours: (meas- ured as Mo). Form: respirable fraction.	2021
Distillates (petroleum), solvent-dewaxed heavy paraffinic	- -	- / 5 / -	CA Alberta Pro- vincial (Canada, 3/2023) [Oil]	OEL 8 hours: Form: Mist	2023
Distillates (petroleum), solvent-dewaxed heavy paraffinic	- -	- / 10 / -	CA Alberta Pro- vincial (Canada, 3/2023) [Oil]	OEL 15 minutes: Form: Mist	2023
Distillates (petroleum), solvent-dewaxed heavy paraffinic	- -	- / 5 / -	CA Ontario Pro- vincial (Canada, 6/2019) [Min- eral oil, exclud- ing metal work- ing fluids (pure, highly and severely refined)]	TWA 8 hours: Form: Inhalable particulate matter	2019
Paraffin oils (petroleum), catalytic dewaxed heavy	- -	- / 5 / -	CA Alberta Pro- vincial (Canada, 3/2023) [Oil]	OEL 8 hours: Form: Mist.	2023
Paraffin oils (petroleum), catalytic dewaxed heavy	- -	- / 10 / -	CA Alberta Pro- vincial (Canada, 3/2023) [Oil]	OEL 15 minutes: Form: Mist	2023
Paraffin oils (petroleum), catalytic dewaxed heavy	- -	- / - / 5	CA Ontario Pro- vincial (Canada, 6/2019) [Min- eral oil, exclud- ing metal work- ing fluids (pure, highly	TWA 8 hours: Form: Inhalable particulate matter	2019



SAFETY DATA SHEET
According to Globally Harmonized System
(GHS)

Version number: 1
Issued: 2026-08-03

Wabco EaseTec M8

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m ³ / F/cm ³	Source	Remark	Year
			and severely refined)]		
propane-1,2-diol	- -	- / 10 / -	CA Ontario Provincial (Canada, 6/2019)	TWA 8 hours: Form: Aerosol only	2019
propane-1,2-diol	- -	- / 155 / -	CA Ontario Provincial (Canada, 6/2019)	TWA 8 hours: . Form: Vapour fraction	2019
propane-1,2-diol	- -	50 / - / -	CA Ontario Provincial (Canada, 6/2019)	TWA 8 hours: . Form: Vapour fraction	2019
calcium dihydroxide	- -	- / 5 / -	CA Alberta Provincial (Canada, 3/2023)	OEL 8 hours	2023
calcium dihydroxide	- -	- / 5 / -	CA British Columbia Provincial (Canada, 9/2024)	TWA 8 hours	2024
calcium dihydroxide	- -	- / 5 / -	CA Ontario Provincial (Canada, 6/2019)	TWA 8 hours	2019
calcium dihydroxide	- -	- / 5 / -	CA Quebec Provincial (Canada, 2/2024)	TWAEV 8 hours	2024
calcium dihydroxide	- -	- / 10 / -	CA Saskatchewan Provincial (Canada, 4/2021)	STEL 15 minutes	2021
calcium dihydroxide	- -	- / 5 / -	CA Saskatchewan Provincial (Canada, 4/2021)	TWA 8 hours	2021



Wabco EaseTec M8

Appropriate engineering controls

Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Keep equipment clean.

Personal Protective Equipment Symbols



Eye / face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.

Other skin protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

A respirator is not needed under normal and intended conditions of product use. Use appropriate respiratory protection if there is a risk of exceeding any exposure limits.

Thermal hazards

Not expected under normal use. Not relevant/applicable due to nature of the product.



Wabco EaseTec M8

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state

Solid. [grease]

Colour

Opaque. Gray

Odour

Hydrocarbon.

Melting point / freezing point

No data available

Boiling point or initial boiling point and boiling range

No data available

Flammability

No data available

Lower and upper explosion limit

Not applicable

Flash point

Not applicable

Auto-ignition temperature

Not applicable.

Decomposition temperature

No data available

pH

No data available

Kinematic viscosity

No data available



Wabco EaseTec M8

Solubility

No data available

Water solubility

Not soluble

Partition coefficient n-octanol/water

Not applicable.

Vapour pressure

No data available

Density and/or relative density

0.96 g/cm³ [25°C (77°F)]

Relative vapour density

No data available

Particle characteristics

No data available

Other information

Vapor density: Not applicable.

SECTION 10: Stability and reactivity

Reactivity

No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

No specific measures identified.

Incompatible materials

Strong oxidizing materials. strong acids. strong alkalis.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.



Wabco EaseTec M8

SECTION 11. Toxicological information

Information on the likely routes of exposure

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix[oral]: 94296.51 mg/kg

Product / Substance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Test animals
calcium carbonate -	LD50	6450 mg/kg	oral	Rat
Distillates (petroleum), solvent-dewaxed heavy paraffinic -	LD50	>2000 mg/kg	Dermal	Rabbit
Distillates (petroleum), solvent-dewaxed heavy paraffinic -	LD50	>5000 mg/kg	oral	Rat
Benzenesulfonic acid, C10-16-alkyl derivs., cal- cium salts -	LD50	>5000 mg/kg	Dermal	Rabbit
Benzenesulfonic acid, C10-16-alkyl derivs., cal- cium salts -	LD50	>5000 mg/kg	oral	Rat
Benzenesulfonic acid, mono- C16-24-alkyl derivs., calcium salts -	LD50	>5000 mg/kg	Dermal	Rabbit
Benzenesulfonic acid, mono- C16-24-alkyl derivs., calcium salts -	LD50	>5000 mg/kg	oral	Rat
Sulfonic acids, petro- leum, calcium salts -	LD50	>5 g/kg	Dermal	Rabbit
Sulfonic acids, petro- leum, calcium salts -	LD50	>5 g/kg	Oral	Rat
calcium dodecylben- zenesulphonate	LD50	1300 mg/kg	Oral	Rat



SAFETY DATA SHEET
According to Globally Harmonized System
(GHS)

Version number: 1
Issued: 2026-08-03

Wabco EaseTec M8

Product / Substance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Test animals
-				
calcium dihydroxide -	LD50	7340 mg/kg	oral	Rat
Benzenamine, N-phenyl- ,reaction products with 2,4,4-trimethylpentene -	LD50	>2000 mg/kg	Dermal	Rabbit
Benzenamine, N-phenyl- ,reaction products with 2,4,4-trimethylpentene -	LD50	>2000 mg/kg	oral	Rat

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes severe eye irritation.

Product / Substance name CAS / EC no.	Result	Value / Dose	Duration of exposure	Species
calcium carbonate -	Severe irritant	750 ug	24 hours	Rabbit
calcium carbonate -	Moderate irritant	500 mg	24 hours	Rabbit
calcium dihydroxide -	Severe irritant	10 mg	-	Rabbit

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility.



Wabco EaseTec M8

STOT-single exposure

Based on available data, the classification criteria are not met.

Product / Substance name CAS / EC no.	Result
calcium dihydroxide -	Respiratory tract irritation [Category 3]

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Routes of exposure

Inhalation : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Eye contact : Causes serious eye irritation.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation Not expected under normal use.

Skin contact: Not expected under normal use.

Eye contact: Pain or irritation, redness, watering.

Ingestion: Not expected under normal use.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Suspected of damaging fertility

Information on other hazards

Other information

None identified.

SECTION 12: Ecological information

Toxicity

Acute toxicity

No known significant effects or critical hazards.

Based on available data, the classification criteria are not met.

Acute fish toxicity



SAFETY DATA SHEET
According to Globally Harmonized System
(GHS)

Version number: 1
Issued: 2026-08-03

Wabco EaseTec M8

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
calcium carbonate -	LC50	>56000 ppm	96 hr	Fish - Gambusia affinis - Adult
Sulfonic acids, petroleum, calcium salts -	LC50	>10000 mg/l	96 hr	Fish - Cyprinodon variegatus
calcium dihydroxide -	LC50	33884.4 µg/l	96 hr	Fish - Clarias gariepinus - Fingerling

Acute algae toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts -	EC50	1000 mg/l	4 d	Algae
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts -	EC50	1000 mg/l	72 hr	Algae
Sulfonic acids, petroleum, calcium salts -	EC50	>100 mg/l	72 hr	Algae - Scenedesmus subspicatus

Acute crustacean toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
Sulfonic acids, petroleum, calcium salts -	EC50	>100 mg/l	48 hr	Daphnia - Daphnia magna

Chronical toxicity

Based on available data, the classification criteria are not met.



SAFETY DATA SHEET
According to Globally Harmonized System
(GHS)

Version number: 1
Issued: 2026-08-03

Wabco EaseTec M8

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
calcium carbonate -	NOEC	16.5 mg/l	30 d	Fish - Rhamdia quelen

Persistence and degradability

Product / Substance name CAS / EC no.	Result
calcium carbonate -	Readily
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts -	Not readily
calcium dodecylbenzenesulphonate -	Readily

Bioaccumulative potential

Product / Substance name CAS / EC no.	LogKow / LogPow	Bioconcentration factor (BCF)	Result
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts -	LogPow: 22.12	-	Potential: High
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene -	LogPow: 5.1	1730	Potential: High

Mobility in soil

Mobility

Not available.

Results of PBT and vPvB assessment

No data available

Endocrine disrupting properties

No data available

Other adverse effects

No known significant effects or critical hazards.



Wabco EaseTec M8

SECTION 13: Disposal considerations

Disposal methods

Disposal considerations

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Empty containers or liners may retain some product residues. Empty containers retain product residue and can be hazardous. Care should be taken when handling emptied containers that have not been cleaned or rinsed out.

SECTION 14: Transport information

UN number

Not regulated.

UN proper shipping name

ADR / RID / ADN proper shipping name

Not regulated.

IMDG proper shipping name

Not regulated.

IATA proper shipping name

Not regulated.

Transport hazard class(es)

Label

Not regulated.

ADR / RID Class

Not regulated.

IMDG Class

Not regulated.

IATA Class

Not regulated.

ADN Class

Not regulated.

Packing group

Not regulated.



Wabco EaseTec M8

Environmental hazards

No

IMDG Marine Pollutant

No

Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure.
Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments

Not available.

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

EU regulations

Not applicable.

National regulations

Canadian NPRI : None of the components are listed.

CEPA Toxic substances : None of the components are listed.

Other regulations, limitations and legal regulations

International regulations:

Montreal Protocol: Not listed.

Stockholm Convention on Persistent Organic Pollutants: Not listed.

Rotterdam Convention on Prior Informed Consent (PIC): Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals: Not listed.

Inventory list:

United States : All components are active or exempted.

Canada : All components are listed or exempted.

Chemical safety assessment

No data available



SAFETY DATA SHEET

According to Globally Harmonized System
(GHS)

Version number: 1

Issued: 2026-08-03

Wabco EaseTec M8

SECTION 16: Other information

Phrase meaning

Eye Irrit. 2 - Eye irritation, hazard category 2

Repr. 2 - Reproductive toxicity, hazard category 2

Acute Tox. 4 - oral - Acute toxicity, oral, hazard category 4

Skin Irrit. 2 - Skin irritation, hazard category 2

Eye Dam. 1 - Serious eye damage, hazard category 1

STOT SE 3 - resp. tract irrit. - Specific Target Organ Toxicity — Single exposure, hazard category 3 - respiratory tract irritation

Aquatic Chronic 3 - Hazardous to the aquatic environment — Chronic hazard category 3

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

H361f Suspected of damaging fertility

H412 Harmful to aquatic life with long lasting effects.

Other

Additional information

Disclaimer:

This product's safety information is provided to assist our customers in assessing compliance with safety/health/ environmental regulations. The information contained herein is based on data available to us and is correct to the best of our knowledge, information and belief at the date of its publication. However, no warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of this data, the results to be obtained from the use thereof, or the hazards connected with the use of the product. Since the use of this product is within the exclusive control of the user, it is the user's obligation to determine the conditions for safe use of the product. Such conditions should comply with all regulations concerning the product. The company referenced in this Safety Data Sheet assumes no liability for any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is attributable to the gross negligence of such company.