

**Stationary applications****List of lubricants TE-ML 23****Table of contents****Page**

<a href="#">1. Approved lubricant classes</a> .....	1
<a href="#">2. Oil and filter change intervals</a> .....	1
<a href="#">3. Low temperatures limits</a> .....	1
<a href="#">4. Explanation of footnotes and comments</a> .....	1
<a href="#">5. Lubricant classes and approved trade products</a> .....	2

**1. Approved lubricant classes**

Product group	Lubricant classes for service fills <sup>(1)</sup>
8TX10500, 8TX10501, 8TX10502	23A, 23B

**2. Oil and filter change intervals**

Lubricant class <sup>(1)</sup>	Oil and filter change interval [h/ year] <sup>(3)</sup>
23A	1500 h 1 x year
23B	1000 h 1 x year

**3. Low temperatures limits**

Lubricant class <sup>(1)</sup>	Viscosity grades	Use at outside temperatures above
23A	10W-40	- 10°C <sup>(2)</sup>
23B	15W-40	0°C <sup>(2)</sup>

**4. Explanation of footnotes and comments**

- (1) Refer to the following pages for approved commercial products.
- (2) At outside temperatures below 0°C, the warm-up provisions described in the manual must be observed.
- (3) Oil and filter change required, depending on what occurs first. Use only ZF original filter elements, ZF order no. 0501 219 453.

Additives of any kind added **later** to the oil change the oil in a manner that is unpredictable, and they are therefore not permitted. No liability of any kind will be accepted by ZF for any damage resulting from the use of such additives.

The list of lubricants TE-ML 23, <b>edition 01.10.2018</b> replaces all previous editions. The current list can be requested from any ZF after-sales service center or accessed on the Internet under <a href="http://www.zf.com/lubricants">www.zf.com/lubricants</a> .	<b>ZF Friedrichshafen AG</b> D-88038 Friedrichshafen <a href="http://www.zf.com/contact">www.zf.com/contact</a>
--	---

**5. Lubricant classes and approved trade products****Lubricant class 23A****Manufacturer (23A)**

SHELL INTERNATIONAL PETROLEUM COMP. LTD, LONDON/GB  
SHELL INTERNATIONAL PETROLEUM COMP. LTD, LONDON/GB

**Trade name (23A)**

SHELL RIMULA R6 M 10W-40  
SHELL RIMULA R6 M 10W-40

**ZF approval number**

ZF001796  
ZF001799

**Lubricant class 23B**

**Manufacturer (23B)**

CHEVRON LUBRICANTS, SAN RAMON, CA/US

**Trade name (23B)**

DELO 400 LE SAE 15W-40

**ZF approval number**

ZF001847