



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: ZF-ECOFLUID A LIFE
Product code: 0671.072.120
0671.072.130

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture: Transmission oil.
Uses advised against: This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

ZF Friedrichshafen AG
ZF Aftermarket
Obere Weiden 12
97424 Schweinfurt
Germany
+49 9721 475 60
www.zf.com/contact

1.4 Emergency telephone number

24/7h Emergency telephone number:
+49 (0)89 19240 Information in German and English

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation , Category 1

H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms:





Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

Signal word:	Warning
Hazard statements	
PHYSICAL HAZARDS:	Not classified as a physical hazard according to CLP criteria.
HEALTH HAZARDS:	H317 May cause an allergic skin reaction.
ENVIRONMENTAL HAZARDS:	Not classified as environmental hazard according to CLP criteria.
Precautionary statements:	
Prevention:	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:	P302 + P352 IF ON SKIN: Wash with plenty of water. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
Storage:	No precautionary phrases.
Disposal:	P501 Dispose of contents/ container to an approved waste disposal plant.
Hazardous components which must be listed on the label:	Contains amine phosphate.

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.
Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
Used oil may contain harmful impurities.
Not classified as flammable but will burn.

3. Composition/information on ingredients

3.2 Mixtures

Chemical nature Synthetic base oil and additives.
Highly refined mineral oil.
The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.
The highly refined mineral oil is only present as additive diluent.

* contains one or more of the following CAS-numbers (REACH registration numbers): 64742-53-6 (01-2119480375-34), 64742-54-7 (01-2119484627-25), 64742-55-8 (01-



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

2119487077-29), 64742-56-9 (01-2119480132-48), 64742-65-0 (01-2119471299-27), 68037-01-4 (01-2119486452-34), 72623-86-0 (01-2119474878-16), 72623-87-1 (01-2119474889-13), 8042-47-5 (01-2119487078-27), 848301-69-9 (01-0000020163-82).

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Long chain alkyl amine thio-phosphate	417-450-2	Flam. Liq.3; H226 Skin Irrit.2; H315 Skin Sens.1A; H317 Eye Irrit.2; H319 Aquatic Chronic3; H412	0,5 - 0,99
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *		Asp. Tox.1; H304	0 - 90

For explanation of abbreviations see section 16.

4. First aid measures

4.1 Description of first aid measures

Protection of first-aiders:

When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

If inhaled:

No treatment necessary under normal conditions of use.
If symptoms persist, obtain medical advice.

In case of skin contact:

Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medi-



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

cal attention.

In case of eye contact:

Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.

If swallowed:

In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms:

Skin sensitisation (allergic skin reaction) signs and symptoms may include itching and/or a rash.

Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment:

Notes to doctor/physician:
Treat symptomatically.

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media:

Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.

5.3 Advice for firefighters

Special protective equipment for fire- Proper protective equipment including



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

fighters: chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: For non emergency personnel:
Avoid contact with skin and eyes.

Emergency responders: For emergency responders:
Avoid contact with skin and eyes.

6.2 Environmental precautions

Environmental precautions: Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up: Slippery when spilt. Avoid accidents, clean up immediately.
Prevent from spreading by making a barrier with sand, earth or other containment material.
Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Chapter 13 of this Safety Data



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

Sheet.

7. Handling and storage

General Precautions:

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.1 Precautions for safe handling

Advice on safe handling:

Avoid prolonged or repeated contact with skin.
Avoid inhaling vapour and/or mists.
When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

Product Transfer:

This material has the potential to be a static accumulator.
Proper grounding and bonding procedures should be used during all bulk transfer operations.

Fire-fighting class:

Fires involving liquids or liquid containing substances. Also includes substances which become liquid at elevated temperatures.

7.2 Conditions for safe storage, including any incompatibilities

Storage class (TRGS 510):

10, Combustible liquids

Other data:

Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
Store at ambient temperature.
Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

Packaging material:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice:	Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

7.3 Specific end use(s)

Specific use(s)	Not applicable
-----------------	----------------

8. Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral	--	TWA	5 mg/m ³	US. ACGIH Threshold Limit Values

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods

<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods

<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazard-



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

ous Substances
<http://www.hse.gov.uk/>
Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany
<http://www.dguv.de/inhalt/index.jsp>
L'Institut National de Recherche et de Sécurité, (INRS), France
<http://www.inrs.fr/accueil>

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection:

If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Approved to EU Standard EN166.

Hand protection:

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protec-



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

tion. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.

Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection:

Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.

Respiratory protection:

No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

protective equipment suppliers.
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.

Thermal hazards: Not applicable

Environmental exposure controls

General advice: Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Liquid
 Colour: amber
 Odour: Slight hydrocarbon
 Odour Threshold: Data not available
 pH: Not applicable

Pour point	-48°C	ASTM D97
Initial boiling point and boiling range	> 280 °C estimated value(s)	
Flash point	240°C	EN ISO 2592
Evaporation rate	Data not available	
Flammability (solid, gas)	Data not available	



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

Upper explosion limit	Typical 10 %(V)	
Lower explosion limit	Typical 1 %(V)	
Vapour pressure	< 0,5 Pa (20 °C) estimated value(s)	
Relative vapour density	> 1 estimated value(s)	
Relative density	0,835 (15°C)	
Density	835 – 840 kg/m3 (15°C)	ISO 12185
Solubility(ies)		
Water solubility	negligible	
Solubility in other solvents	Data not available	
Partition coefficient: n-octanol/water	Pow: > 6 (based on information on similar products)	
Auto-ignition temperature	> 320°C	
Viscosity, dynamic	Data not available	
Viscosity, kinematic	68 mm2/s (40°C) 10 mm2/s (100°C)	ASTM D445
Explosive properties	Not classified	
Oxidizing properties	Data not available	

9.2 Other information

Conductivity: This material is not expected to be a static accumulator.

Decomposition temperature: Data not available



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

10. Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following subparagraph.

10.2 Chemical stability:

Stable.
No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions:

Reacts with strong oxidising agents.

10.4 Conditions to avoid:

Extremes of temperature and direct sunlight

10.5 Incompatible materials:

Strong oxidising agents.

10.6 Hazardous decomposition products:

Hazardous decomposition products are not expected to form during normal storage.

11. Toxicological information

11.1 Information on toxicological effects

Basis for assessment:

Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity:

LD50 rat: > 5.000 mg/kg

Remarks: Expected to be of low toxicity

Acute inhalation toxicity:

Remarks: Not considered to be an inhalation hazard under normal conditions of use.

Acute dermal toxicity:

LD50 Rabbit: > 5.000 mg/kg

Remarks: Expected to be of low toxicity



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

Respiratory or skin sensitisation

Product:

Remarks: For skin sensitisation: Expected to be a skin sensitizer.

Remarks: For respiratory sensitisation: Not expected to be a sensitizer.

Germ cell mutagenicity

Product:

Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification

Reproductive toxicity

Product:

Remarks: Not expected to impair fertility.

Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Summary on evaluation of the CMR properties

Germ cell mutagenicity – Assessment: This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity – Assessment: This product does not meet the criteria for classification in categories 1A/1B.

Reproductive toxicity – Assessment: This product does not meet the criteria for classification in categories 1A/1B.

12. Ecological information

12.1 Toxicity

Basis for assessment: Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). (LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

Product:
Toxicity to fish (Acute toxicity): Remarks: Expected to be practically non toxic:
LL/EL/IL50 > 100 mg/l

Toxicity to crustacean (Acute toxicity) Remarks: Expected to be practically non toxic:
LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic plants (Acute toxicity) Remarks: Expected to be practically non toxic:
LL/EL/IL50 > 100 mg/l



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

Toxicity to fish (Chronic toxicity) Remarks: Data not available

Toxicity to crustacean (Chronic toxicity) Remarks: Data not available

Toxicity to microorganisms (Acute toxicity) Remarks: Data not available

12.2 Persistence and degradability

Product: Remarks: Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but contains components that may persist in the environment.
Biodegradability

12.3 Bioaccumulative potential

Product: Remarks: Contains components with the potential to bioaccumulate.
Bioakkumulation Pow: > 6
Partition coefficient: n-octanol/water Remarks: (based on information on similar products)

12.4 Mobility in soil

Product: Remarks: Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile.
Mobility Remarks: Floats on water.

12.5 Results of PBT and vPvB assessment

Product: This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.
Assessment

12.6 Other adverse effects

Product: Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential. Poorly soluble mixture. May cause physical fouling of aquatic organisms.
Additional ecological information

13. Disposal considerations

13.1 Waste treatment methods

Product: Recover or recycle if possible.
It is the responsibility of the waste genera-



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

tor to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Waste, spills or used product is dangerous waste.

Contaminated packaging:

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation
Waste catalogue

to apply to

EU Waste Disposal Code (EWC):

13 02 06*

Remarks:

Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Classification of waste is always the responsibility of the end user.

14 Transport information

14.1 UN number

14.2 Proper shipping name

14.3 Transport hazard class

14.4 Packing group

CDNI Inland Water Waste Agreement NST 3411 Mineral Lubricating Oils

14.5 Environmental hazards

14.6 Special precautions for user



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

Remarks: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category: Not applicable
Ship type: Not applicable
Product name: Not applicable
Special precautions: Not applicable
Additional Information: MARPOL Annex 1 rules apply for bulk shipments by sea.

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorization (Annex XIV) Product is not subject to Authorisation under REACH.

Water contaminating class (Germany): WGK 2 water endangering
Remarks: Classification according VwVwS, Annex 2.

Volatile organic compounds: 0 %

Other regulations: Technische Anleitung Luft: Product not listed by name.
Observe section 5.2.5 in connection with section 5.4.9
Product is subject to Vorgaben der Betriebs-Sicherheits-Verordnung (BetrSichV).

Compliance with paragraph 22 of Youth Employment Law.
Compliance with Maternity Protection Act paragraphs 4 and 5.

The components of this product are reported in the following inventories:

EINECS: All components listed or polymer exempt.
TSCA: All components listed.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

16. Other information

REGULATION (EC) No 1272/2008

Skin sensitisation, Category 1, H317

Classification procedure

Expert judgement and weight of evidence determination.

Full text of H-Statements

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H412 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation

Abbreviations and Acronyms: The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists
ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
AICS = Australian Inventory of Chemical Substances
ASTM = American Society for Testing and Materials
BEL = Biological exposure limits
BTEX = Benzene, Toluene, Ethylbenzene, Xylenes
CAS = Chemical Abstracts Service
CEFIC = European Chemical Industry Council
CLP = Classification Packaging and Labelling



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

COC = Cleveland Open-Cup
DIN = Deutsches Institut für Normung
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
DSL = Canada Domestic Substance List
EC = European Commission
EC50 = Effective Concentration fifty
ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals
ECHA = European Chemicals Agency
EINECS = The European Inventory of Existing Commercial Chemical Substances
EL50 = Effective Loading fifty
ENCS = Japanese Existing and New Chemical Substances Inventory
EWC = European Waste Code
GHS = Globally Harmonised System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IC50 = Inhibitory Concentration fifty
IL50 = Inhibitory Level fifty
IMDG = International Maritime Dangerous Goods
INV = Chinese Chemicals Inventory
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables
KECI = Korea Existing Chemicals Inventory
LC50 = Lethal Concentration fifty
LD50 = Lethal Dose fifty per cent.
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading
LL50 = Lethal Loading fifty
MARPOL = International Convention for the Prevention of Pollution From Ships
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level
OE_HP V = Occupational Exposure - High Production Volume
PBT = Persistent, Bioaccumulative and Toxic
PICCS = Philippine Inventory of Chemicals and Chemical Substances
PNEC = Predicted No Effect Concentration
REACH = Registration Evaluation And Authorisation Of Chemicals



Trade name: ZF-ECOFLUID A LIFE

ZF Aftermarket

RID = Regulations Relating to International Carriage of Dangerous Goods by Rail
SKIN_DES = Skin Designation
STEL = Short term exposure limit
TRA = Targeted Risk Assessment
TSCA = US Toxic Substances Control Act
TWA = Time-Weighted Average
vPvB = very Persistent and very Bioaccumulative

Further information

Training advice

Provide adequate information, instruction and training for operators.

Other information:

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.