

Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: ZF EcoFluid Life Plus

Product code: AA01.320.098

AA01.320.099

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture: Transmission oil.

Uses advised against:

This product must not be used in applica-

tions other than those listed in Section 1 without first seeking the advice of the

supplier.

1.3 Details of the supplier of the safety data sheet

ZF Friedrichshafen AG ZF Aftermarket Obere Weiden 12 97424 Schweinfurt Germany +49 9721 475 60 www.zf.com/contact

1.4 Emergency telephone number

24/7h Emergency telephone number:

+49 (0)89 19240 Information in German and English

2. Hazards identification

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms: No Hazard Symbol required

Signal word:

No signal word

Hazard statements

PHYSICAL HAZARDS: Not classified as a physical hazard

according to CLP criteria.

ZF Friedrichshafen AG • ZF Aftermarket Obere Weiden 12, 97424 Schweinfurt, Germany

ket © ZF Friedrichshafen AG

Phone: +49 9721 4756-0 www.zf.com/contact

Revision Date: 15.01.2020



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

HEALTH HAZARDS: Not classified as a health hazard under CLP

criteria.

ENVIRONMENTAL HAZARDS: Not classified as environmental hazard

according to CLP criteria.

Precautionary statements:

Prevention: No precautionary phrases.

Response: No precautionary phrases.

Storage: No precautionary phrases.

Disposal: No precautionary phrases.

Safety data sheet available on request.

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

3. Composition/information on ingredients

3.2 Mixtures

Chemical nature Synthetic base oil and additives.

Highly refined mineral oil.

The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346. The highly refined mineral oil is only pre-

sent as additive diluent.

Hazardous components

Chemical name	CAS-No. EC-No.	Classification (REGU-	Concentration
	Registration	LATION (EC) No	[%]
	number	1272/2008)	
Distillates (Fischer	848301-69-9	Asp. Tox.1; H304	0 - 90
Tropsch), heavy,	482-220-0 / 01-		
C18-50 -branched,	0000020163-82		
cvclic and linear			

For explanation of abbreviations see section 16.

© ZF Friedrichshafen AG Revision Date: 15.01.2020



ZF Aftermarket

4. First aid measures

4.1 Description of first aid measures

General advice: Not expected to be a health hazard when

used under normal

conditions.

Protection of first-aiders: When administering first aid, ensure that

you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

If inhaled: No treatment necessary under normal

conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact: Remove contaminated clothing. Flush ex-

posed area with water and follow by wash-

ing with soap if available.

If persistent irritation occurs, obtain medi-

cal attention.

In case of eye contact: Flush eye with copious quantities of water.

If persistent irritation occurs, obtain medi-

cal attention.

If swallowed:

In general no treatment is necessary unless

large quantities are swallowed, however,

get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms: Oil acne/folliculitis signs and symptoms

may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting

and/or diarrhoea.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment: Notes to doctor/physician:

Treat symptomatically.

5. Firefighting measures

5.1 Extinguishing media

© ZF Friedrichshafen AG Revision Date: 15.01.2020



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

Suitable extinguishing media: Foam, water spray or fog. Dry chemical

powder, carbon dioxide, sand or earth may

be used for small fires only.

Unsuitable extinguishing media: Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting: Hazardous combustion products may in-

clude: A complex mixture of airborne solid

and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs.

Unidentified organic and inorganic

compounds.

5.3 Advice for firefighters

Special protective equipment for fire-

fighters:

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards

(e.g. Europe: EN469).

Specific extinguishing methods: Use extinguishing measures that are ap-

propriate to local circumstances and the

surrounding environment.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: For non emergency personnel:

Avoid contact with skin and eyes.

Emergency responders: For emergency responders:

Avoid contact with skin and eyes.

6.2 Environmental precautions

Environmental precautions: Use appropriate containment to avoid envi-

ronmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appro-

priate barriers.

© ZF Friedrichshafen AG Revision Date: 15.01.2020



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up:

Slippery when spilt. Avoid accidents, clean

up immediately.

Prevent from spreading by making a barrier with sand, earth or other containment ma-

terial.

Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and

dispose of properly

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

7. Handling and storage

General Precautions:

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.1 Precautions for safe handling

Advice on safe handling:

Avoid prolonged or repeated contact with

skin.

Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper han-

dling equipment should be used.

Properly dispose of any contaminated rags or cleaning materials in order to prevent

fires

Product Transfer: This material has the potential to be a stat-

ic accumulator.

Proper grounding and bonding procedures should be used during all bulk transfer op-

erations.

© ZF Friedrichshafen AG Revision Date: 15.01.2020

Phone: +49 9721 4756-0 www.zf.com/contact



ZF Aftermarket

Fire-fighting class: Fires involving liquids or liquid containing

substances. Also includes substances which become liquid at elevated

temperatures.

7.2 Conditions for safe storage, including any incompatibilities

Storage class (TRGS 510): 10, Combustible liquids

Other data: Keep container tightly closed and in a cool,

well-ventilated place. Use properly labeled

and closable containers.

Store at ambient temperature.

Refer to section 15 for any additional specific legislation covering the packaging and

storage of this product.

Packaging material: Suitable material: For containers or con-

tainer linings, use mild steel or high density

polyethylene.

Unsuitable material: PVC.

Container Advice: Polyethylene containers should not be ex-

posed to high temperatures because of

possible risk of distortion.

7.3 Specific end use(s)

Specific use(s) Not applicable

8. Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of	Control para-	Basis
		exposure)	meters	
Oil mist, mine-		TWA	5 mg/m³	US. ACGIH
ral				Threshold
				Limit Values

Biological occupational exposure limits

No biological limit allocated.

© ZF Friedrichshafen AG Revision Date: 15.01.2020



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods

http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods

http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances

http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany

http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France

http://www.inrs.fr/accueil

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping

ZF Friedrichshafen AG • ZF Aftermarket Obere Weiden 12, 97424 Schweinfurt, Germany Phone: +49 9721 4756-0 © ZF Friedrichshafen AG Revision Date: 15.01.2020



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection:

If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Approved to EU Standard EN166.

Hand protection:

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.

Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove

www.zf.com/contact



ZF Aftermarket

make and model.

Skin and body protection: Skin protection is not ordinarily required

beyond standard work clothes.

It is good practice to wear chemical re-

sistant gloves.

Respiratory protection: No respiratory protection is ordinarily re-

quired under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering

controls do not maintain airborne

concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory

protective equipment suppliers.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.

Thermal hazards: Not applicable

Environmental exposure controls

General advice: Take appropriate measures to fulfill the

requirements of relevant environmental

protection legislation. Avoid

contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Pour point



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

DIN ISO 3016

Appearance: Clear, bright liquid.

Colour: clear

Odour: Slight hydrocarbon
Odour Threshold: Data not available
pH: Not applicable

Initial boiling point and boiling range	> 280 °C estimated value(s)	
Flash point	230 - 245°C	Unspecified
Evaporation rate	Data not available	
Flammability (solid, gas)	Data not available	
Upper explosion limit	Typical 10 %(V)	
Lower explosion limit	Typical 1 %(V)	
Vapour pressure	< 0,5 Pa (20 °C) estimated value(s)	
Relative vapour density	> 1 estimated value(s)	
Relative density	0,828 - 0,836 (15°C)	
Density	828 - 836 kg/m³	ISO 12185
Solubility(ies)		
Water solubility	negligible	
Solubility in other solvents	Data not available	
Partition coefficient: n- octanol/water	Pow: > 6 (based on information on similar products)	
Auto-ignition temperature	> 320°C	

<=57°C



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

Viscosity, dynamic	Data not available	
Viscosity, kinematic	6,8 - 7,5 mm²/s (100°C)	ASTM D445
Explosive properties	Not classified	
Oxidizing properties	Data not available	

9.2 Other information

Conductivity: This material is not expected to be a static

accumulator.

Decomposition temperature: Data not available

10. Stability and reactivity

10.1 Reactivity The product does not pose any further re-

activity hazards in addition to those listed

in the following subparagraph.

10.2 Chemical stability: Stable.

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions: Reacts with strong oxidising agents.

10.4 Conditions to avoid: Extremes of temperature and direct sun-

light

10.5 Incompatible materials: Strong oxidising agents.

10.6 Hazardous decomposition products: Hazardous decomposition products are not

expected to form during normal storage.

11. Toxicological information

11.1 Information on toxicological effects

Basis for assessment: Information given is based on data on the

components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

product as a whole, rather than for individ-

ual component(s).

Information on likely routes of expo-

sure

Skin and eye contact are the primary routes of exposure although exposure may

occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity: LD50 rat: > 5.000 mg/kg

Remarks: Expected to be of low toxicity

Acute inhalation toxicity: Remarks: Not considered to be an inhala-

tion hazard under normal conditions of

use.

Acute dermal toxicity: LD50 Rabbit: > 5.000 mg/kg

Remarks: Expected to be of low toxicity

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

Respiratory or skin sensitisation

Product:

Remarks: For respiratory and skin sensitisation: Not expected to be a sensitiser.

Germ cell mutagenicity

Product:

Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification

Reproductive toxicity

Product:

© ZF Friedrichshafen AG Revision Date: 15.01.2020



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

Remarks: Not expected to impair fertility. Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

Remarks: Classifications by other authorities under varying regulatory frameworks

may exist.

Summary on evaluation of the CMR properties

Germ cell mutagenicity – Assessment: This product does not meet the criteria for

classification in categories 1A/1B.

Carcinogenicity – Assessment: This product does not meet the criteria for

classification in categories 1A/1B.

Reproductive toxicity – Assessment: This product does not meet the criteria for

classification in categories 1A/1B.

12. Ecological information

12.1 Toxicity

Basis for assessment: Ecotoxicological data have not been de-

termined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated oth-

erwise, the data presented is

representative of the product as a whole,

© ZF Friedrichshafen AG Revision Date: 15.01.2020

www.zf.com/contact



Trade name: ZF EcoFluid Life Plus

7F Aftermarket

rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to

prepare aqueous test extract).

Product: Remarks: Expected to be practically non

Toxicity to fish (Acute toxicity):

LL/EL/IL50 > 100 mg/l

Toxicity to crustacean (Acute toxicity) Remarks: Expected to be practically non

toxic:

LL/EL/IL50 > 100 mg/l

toxicity)

Toxicity to algae/aquatic plants (Acute Remarks: Expected to be practically non

toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic toxicity) Remarks: Data not available

Toxicity to crustacean (Chronic

toxicity)

Remarks: Data not available

Toxicity to microorganisms

(Acute toxicity)

Remarks: Data not available

12.2 Persistence and degradability

Product:

Biodegradability

Remarks: Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but contains components that may persist in

the environment.

12.3 **Bioaccumulative potential**

> Product: Remarks: Contains components with the

Bioakkumulation potential to bioaccumulate.

Partition coefficient: n-octanol/water Pow: > 6 Remarks: (based on information)

on similar products)

12.4 Mobility in soil

> Product: Remarks: Liquid under most environmental conditions. If it enters soil, it will adsorb to Mobility

soil particles and will not be mobile.

Remarks: Floats on water.

12.5 Results of PBT and vPvB assessment

> Product: This mixture does not contain any REACH Assessment registered substances that are assessed to

> > be a PBT or a vPvB.

Phone: +49 9721 4756-0 www.zf.com/contact

© ZF Friedrichshafen AG Revision Date: 15.01.2020



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

12.6 Other adverse effects

Product:

Additional ecological information

Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential. Poorly soluble mixture. May cause physical fouling of aquatic organisms.

13. Disposal considerations

13.1 Waste treatment methods

Product: Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.

Waste, spills or used product is dangerous

waste.

Contaminated packaging: Dispose in accordance with prevailing reg-

ulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

to apply to

Local legislation Waste catalogue

EU Waste Disposal Code (EWC): 13 02 06*

Remarks: Disposal should be in accordance with ap-

plicable regional, national, and local laws

and regulations.

Classification of waste is always the re-



ZF Aftermarket

sponsibility of the end user.

14 Transport information

14.1 UN number

ADN Not regulated as a dangerous good ADR Not regulated as a dangerous good RID Not regulated as a dangerous good IMDG Not regulated as a dangerous good IATA Not regulated as a dangerous good Not regulated as a dangerous good

14.2 Proper shipping name

ADN
ADR
Not regulated as a dangerous good
RID
Not regulated as a dangerous good

14.3 Transport hazard class

ADN Not regulated as a dangerous good ADR Not regulated as a dangerous good RID Not regulated as a dangerous good IMDG Not regulated as a dangerous good IATA Not regulated as a dangerous good

14.4 Packing group

ADN
CDNI Inland Water Waste Agreement
ADR
RID
IMDG
Not regulated as a dangerous good
NST 3411 Mineral Lubricating Oils
Not regulated as a dangerous good

14.5 Environmental hazards

ADN Not regulated as a dangerous good
ADR Not regulated as a dangerous good
RID Not regulated as a dangerous good
IMDG Not regulated as a dangerous good

14.6 Special precautions for user

Remarks:

Special Precautions: Refer to Chapter 7,
Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with

© ZF Friedrichshafen AG

transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Revision Date: 15.01.2020



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

Pollution category:

Ship type:

Product name:

Special precautions:

Not applicable

Not applicable

Not applicable

Additional Information: MARPOL Annex 1 rules apply for bulk

shipments by sea.

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to

authorization (Annex XIV)

Product is not subject to Authorisation un-

der REACH.

Water contaminating class

(Germany):

WGK 2 water endangering

Remarks: Classification according VwVwS,

Annex 2.

0 %

Volatile organic compounds:

Other regulations: Technische Anleitung Luft: Product not

listed by name.

Observe section 5.2.5 in connection with

section 5.4.9

Product is subject to Vorgaben der Betriebs-SicherheitsVerordnung (BetrSichV). Youth Employment Law Not Applicable. Maternity Protection Act Not Applicable

The components of this product are reported in the following inventories:

EINECS: All components listed or polymer exempt.

TSCA: All components listed.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other information

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

Full text of other abbreviations

© ZF Friedrichshafen AG Revision Date: 15.01.2020



Trade name: ZF EcoFluid Life Plus

7F Aftermarket

Asp. Tox. Aspiration hazard

Abbreviations and Acronyms:

The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Sub-

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology

and Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing

Commercial Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classi-

fication and Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous

Goods

www.zf.com/contact



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

INV = Chinese Chemicals Inventory IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables KECI = Korea Existing Chemicals Inventory LC50 = Lethal Concentration fifty LD50 = Lethal Dose fifty per cent. LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading LL50 = Lethal Loading fifty MARPOL = International Convention for the Prevention of Pollution From Ships NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level OE HPV = Occupational Exposure - High **Production Volume** PBT = Persistent, Bioaccumulative and Toxic PICCS = Philippine Inventory of Chemicals and Chemical Substances PNEC = Predicted No Effect Concentration REACH = Registration Evaluation And Authorisation Of Chemicals RID = Regulations Relating to International Carriage of Dangerous Goods by Rail SKIN DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative

Further information

Training advice

Provide adequate information, instruction and

training for operators.

Other information:

No Exposure Scenario annex is attached to this safety data sheet. It is a non-classified mixture containing hazardous substances as detailed in Section 3; relevant information from Exposure Scenarios for the hazardous substances contained have been integrated into the core sections 1-16 of this SDS. A vertical bar (|) in the left margin indicates

an amendment from the previous version.

Sources of key data used to

The quoted data are from, but not limited to,

© ZF Friedrichshafen AG



Trade name: ZF EcoFluid Life Plus

ZF Aftermarket

compile the Safety Data Sheet

one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Revision Date: 15.01.2020

© ZF Friedrichshafen AG