According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Product name: ZF LifeguardFluid CVT 1

ZF Aftermarket

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: ZF LifeguardFluid CVT 1

Product code: 5961.308.626

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricant

Uses advised against:

No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

ZF Friedrichshafen AG ZF Aftermarket Obere Weiden 12 97424 Schweinfurt Germany +49 9721 475 60 www.zf.com/contact

1.4 Emergency telephone number:

24/7h Emergency telephone number:

+49 (0)89 19 240 (Information in German and English)

2. Hazards identification

2.1 Classification of the substance or mixture

The product has not been classified as hazardous, but needs to be labelled according to regulation GB-CLP.

Classification according to GB-CLP.

Hazard summary

Physical Hazards: No data available.

2.2 Label Elements EUH210: Safety data sheet available on

request.

2.3 Other hazards:

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective

© ZF Friedrichshafen AG Stand: 27.09.2023

Phone: +49 9721 4756-0 www.zf.com/contact

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Product name: ZF LifeguardFluid CVT 1

ZF Aftermarket

equipment (item 8) are kept. The product may not be released into the environment without control.

3. Composition/information on ingredients

3.2 Mixtures

General information: Mixture containing severely refined base oils and additives.

Chemical	Identifier	Concentration *	UK-REACH
name			Registration No.
base oil, low viscous	EINECS: 276-738-4	20,00% - <50,00%	
Base oil, low viscous	EINECS: 265-158-7	1,00% - <10,00%	
Base oil, low viscous	EINECS: 276-737-9	1,00% - <10,00%	
base oil, paraffinic	EINECS: 265-169-7	1,00% - <10,00%	
alkarylamine, longchained	EINECS: 253-249-4	1,00% - <5,00%	

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Identifier	Classification	
base oil, low	EINECS: 276-738-4	GBCLP:	Asp. Tox. 1;H304
viscous			
Base oil, low viscous	EINECS: 265-158-7	GBCLP:	Asp. Tox. 1;H304
Base oil, low viscous	EINECS: 276-737-9	GBCLP:	Asp. Tox. 1;H304
base oil, paraffinic	EINECS: 265-169-7	GBCLP:	Asp. Tox. 1;H304
alkarylamine, longchained	EINECS: 253-249-4	GBCLP:	Aquatic Chronic 4;H413

GB-CLP

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation GB-CLP.

4. First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Product name: ZF LifeguardFluid CVT 1

ZF Aftermarket

symptoms.

Eye contact: Promptly wash eyes with plenty of water

while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and

delayed:

May cause skin and eye irritation.

4.3 Indication of any immediate medical attention and special

treatment needed

Get medical attention if symptoms occur.

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

CO2, fire extinguishing powder or fog like

water spraying. Extinguish larger

fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing

media:

Water with a full water jet.

5.2 Special hazards arising

from the substance or mixture:

During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire fighting procedures:

Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter

drains.

Special protective equipment for

fire-fighters:

www.zf.com/contact

Self-contained breathing apparatus and full protective clothing must be worn in case of

fire.

© ZF Friedrichshafen AG Stand: 27.09.2023

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Product name: ZF LifeguardFluid CVT 1



ZF Aftermarket

6. Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures:

In case of spills, beware of slippery floors

and surfaces.

6.2 Environmental Precautions:

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent from spreading (e.g. by binding or oil barriers). Environmental manager must be informed of all major spillages. Do not allow to enter drainage system, surface or

ground water.

6.3 Methods and material for containment and cleaning

up:

Absorb with liquid-binding material (sand, diatomite, acidbinders, universal

binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

6.4 Reference to other sections:

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

7. Handling and storage:

7.1 Precautions for safe handling:

Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.

7.2 Conditions for safe storage, including any incompatibilities:

Local regulations concerning handling and storage of waterpolluting products have to

be followed. Do not heat up to temperatures close to the flash point.

7.3 Specific end use(s): Not applicable

Storage Class: 10, Combustible liquids

8. Exposure controls/personal protection

8.1 Control Parameters

www.zf.com/contact

© ZF Friedrichshafen AG Stand: 27.09.2023

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Product name: ZF LifeguardFluid CVT 1



ZF Aftermarket

Occupational Exposure Limits

None of the components have assigned exposure limits.

8.2 Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information:

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to inhandling the chemicals or the mineral oil products.

Eye/face protection:

Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or

face shield.

Skin protection Hand Protection:

Material: Nitrile butyl rubber (NBR). Min. Breakthrough time: >= 480 min

Recommended thickness of the material: >= 0,38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective

gloves and has to be observed.

ZF Friedrichshafen AG • ZF Aftermarket Obere Weiden 12, 97424 Schweinfurt, Germany Phone: +49 9721 4756-0

www.zf.com/contact

© ZF Friedrichshafen AG Stand: 27.09.2023

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Product name: ZF LifeguardFluid CVT 1

ZF Aftermarket

Other: Do not carry cleaning cloths impregnated

with the product in trouser pockets. Wear

suitable protective clothing.

Respiratory Protection: Ensure good ventilation/exhaustion at the

workplace. Avoid breathing vapour/ aero-

sol.

Thermal hazards: Not known.

Hygiene measures: Always observe good personal hygiene

measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove

contaminants. Discard contaminated footwear that cannot be cleaned.

Environmental Controls: No data available.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: liquid Form: liquid Color: Amber

Odor: Characteristic

pH: substance/mixture is non-soluble (in water)

Freezing point: not determined Boiling Point: not determined

Flash Point: 208 °C

Evaporation Rate: Not applicable for mixtures

Flammability (solid, gas): not determined

Flammability Limit - Upper (%)-:

Flammability Limit - Lower (%)-:

Vapor pressure:

Relative vapor density:

Not applicable for mixtures

Not applicable for mixtures

Not applicable for mixtures

Density: 0,85 g/ml (15,00 °C)

Solubility(ies)

Solubility in Water: Insoluble in water Solubility (other): No data available.

Partition coefficient (n-octanol/water): Not applicable for mixtures

ZF Friedrichshafen AG • ZF Aftermarket Obere Weiden 12, 97424 Schweinfurt, Germany © ZF Friedrichshafen AG

Phone: +49 9721 4756-0 www.zf.com/contact

Stand: 27.09.2023

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Product name: ZF LifeguardFluid CVT 1

ZF Aftermarket

Autoignition Temperature: not determined Decomposition Temperature: not determined

Kinematic viscosity: 34 mm²/s (40,00 °C)

Explosive properties: Value not relevant for classification Oxidizing properties: Value not relevant for classification

Particle characteristics: Not applicable

9.2 Other information No data available.

10. Stability and reactivity

10.1 Reactivity: Stable under normal use conditions.

10.2 Chemical Stability: Stable under normal use conditions.

10.3 Possibility of hazardous Stable under normal use conditions.

reactions:

Products:

10.4 Conditions to avoid: Stable under normal use conditions.

10.5 Incompatible Materials: Strong oxidizing substances. Strong acids.

Strong bases.

10.6 Hazardous Decomposition Thermal decomposition or combustion

may liberate carbon oxides and other toxic

gases or vapors.

11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

base oil, low viscous LD 50 (Rat): > 5.000 mg/kg (OECD 401)

Base oil, low viscous LD 50 (Rat): > 5.000 mg/kg

Base oil, low viscous LD 50 (Rat): > 5.001 mg/kg (OECD 401)

alkarylamine, longchained LD 50 (Rat): > 5.000 mg/kg (OECD 401)

Phone: +49 9721 4756-0 www.zf.com/contact

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ZF Aftermarket

Product name: ZF LifeguardFluid CVT 1

Dermal

Product:

ATEmix: 92.949 mg/kg

Specified substance(s)

Base oil, low viscous LD 50 (Rabbit): > 5.000 mg/kg

Base oil, low viscous LD 50 (Rabbit): > 5.000 mg/kg (OECD

402)

Inhalation

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

Base oil, low viscous LC 50 (Rat, 4 h): > 5 mg/l

Base oil, low viscous LC 50 (Rat, 4 h): > 5,53 mg/l

Dust and mist

Skin Corrosion/Irritation:

Product:

Based on available data, the classification criteria are not met.

Specified substance(s)

alkarylamine, longchained OECD 404 (Rabbit):

Not irritant.

Serious Eye Damage/Eye Irritation:

Product:

Based on available data, the classification criteria are not met.

Specified substance(s)

alkarylamine, longchained OECD 405 (Rabbit):

Not irritant.

Respiratory or Skin Sensitization:

Product:

Skin sensitizer: Based on available data, the classification criteria are not

met.

Respiratory sensitizer: Based on available data, the classification criteria

are not met.

Specified substance(s)

alkarylamine, longchained No sensitizing effect (guinea pig); OECD

406

Phone: +49 9721 4756-0 www.zf.com/contact

© ZF Friedrichshafen AG Stand: 27.09.2023

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758





ZF Aftermarket

Germ Cell Mutagenicity

Product:

Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product:

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product:

Based on available data, the classification criteria are not met.

Aspiration Hazard

Product:

Based on available data, the classification criteria are not met.

Other adverse effects: No data available.

12. Ecological information

12.1 Toxicity

Acute toxicity Based on available data, the classification

Product: criteria are not met.

Fish

Specified substance(s)

base oil, low viscous LC 50 (Fish, 96 h): > 100 mg/l (OECD 203)

alkarylamine, longchained LC 50 (Zebra Fish, 96 h): > 100 mg/l

(OECD 203)

Aquatic Invertebrates Specified substance(s)

base oil, low viscous EL50 (Water Flea, 48 h): > 10.000 mg/l

(OECD 202)

Base oil, low viscous EL50 (Water Flea, 48 h): > 10.000 mg/l

alkarylamine, longchained EC 50 (Water Flea, 48 h): > 100 mg/l

ZF Friedrichshafen AG • ZF Aftermarket Obere Weiden 12, 97424 Schweinfurt, Germany Phone: +49 9721 4756-0 © ZF Friedrichshafen AG Stand: 27.09.2023

www.zf.com/contact 9/13

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Product name: ZF LifeguardFluid CVT 1

ZF Aftermarket

(OECD 202)

Chronic Toxicity Based on available data, the classification

Product criteria are not met.

Fish

Specified substance(s)

base oil, low viscous NOEC (Fish, 14 d): > 1.000 mg/l

Base oil, low viscous NOEL (Fish, 14 d): 1.000 mg/l

Aquatic Invertebrates Specified substance(s)

base oil, low viscous NOEC (Water Flea, 21 d): 10 mg/l (OECD

211)

Base oil, low viscous NOEC (Water Flea, 21 d): 10 mg/l (OECD

211)

Toxicity to Aquatic Plants Specified substance(s)

base oil, low viscous NOEC (Alga, 72 h): > 100 mg/l (OECD

201)

Base oil, low viscous NOEC (Alga, 72 h): > 100 mg/l (OECD

201)

alkarylamine, longchained EC 50 (Alga, 72 h): > 100 mg/l (OECD

201)

12.2 Persistence and Degradability

Biodegradation

Product: Not applicable for mixtures

Specified substance(s)

alkarylamine, longchained 1 % (28 d) Not readily degradable.

12.3 Bioaccumulative potential

Product: Not applicable for mixtures

12.4 Mobility in soil:

Product: Not applicable for mixtures

12.5 Results of PBT and vPvB The product does not contain any

assessment: substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects: Experimental data has shown that the

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Product name: ZF LifeguardFluid CVT 1

ZF Aftermarket

concentration of the potentially aquatic toxic components present in this product is not harmful to aquatic

organisms.

Water Hazard Class

(WGK):

WGK 1: slightly water-endangering.

13. Disposal considerations

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable

regulations.

Disposal methods: Discharge, treatment, or disposal may be

subject to national, state, or local

laws.

List of Waste (LoW) Codes 13 02 05*: mineral-based non-chlorinated

engine, gear and lubricating oils

14 Transport information

ADR/RID

14.1 UN Number:

14.2 UN Proper Shipping Name: --

14.3 Transport Hazard Class(es)

Class: Non-dangerous goods

Label(s): --Hazard No. (ADR): ---

Tunnel restriction code: --

14.4 Packing Group: --

14.5 Environmental hazards: -- 14.6 Special precautions for user: --

IMDG

14.1 UN Number: - 14.2 UN Proper Shipping Name: -

14.3 Transport Hazard Class(es)

Class: Non-dangerous goods

Label(s): -EmS No.: -14.4 Packing Group: --

14.5 Environmental hazards:

ZF Friedrichshafen AG • ZF Aftermarket Obere Weiden 12, 97424 Schweinfurt, Germany © ZF Friedrichshafen AG Stand: 27.09.2023

Phone: +49 9721 4756-0 www.zf.com/contact 11/13

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Product name: ZF LifeguardFluid CVT 1

ZF Aftermarket

14.6 Special precautions for user:

IATA

14.1 UN Number: 14.2 Proper Shipping Name:

14.3 Transport Hazard Class(es):

Class: Non-dangerous goods

Label(s): 14.4 Packing Group: 14.5 Environmental hazards: 14.6 Special precautions for user:

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the sub-15.1 stance or mixture:

GB Regulations

The Ozone-Depleting Substances none and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit)

Regulations 2019:

The Persistent Organic none Pollutants (Amendment)

(EU Exit) Regulations 2020:

15.2 **Chemical safety assessment:**

No Chemical Safety Assessment has been carried out.

DIRECTIVE Control of Major Accident Hazards Regulations 2015

Not applicable

16. Other information

Revision Information: Vertical lines in the margin indicate an

amendment.

Wording of the H-statements in section 2 and 3

May be fatal if swallowed and enters airways. H304


May cause long lasting harmful effects to aquatic life. H413

ZF Friedrichshafen AG • ZF Aftermarket Obere Weiden 12, 97424 Schweinfurt, Germany

© ZF Friedrichshafen AG Stand: 27.09.2023

Phone: +49 9721 4756-0 www.zf.com/contact 12/13

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758





7F Aftermarket

Other information: The classification complies with the current

GB lists: however, it has been supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: On the basis of test data; Calculation Method; Bridging Principle "Substantially similar

mixtures"; Expert Judgement

Disclaimer:

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.

www.zf.com/contact

© ZF Friedrichshafen AG

13/13

Stand: 27.09.2023