

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.11.2013

Version number 2

Revision: 14.11.2013

1 Identification of the substance/mixture and of the company/ undertaking

- **Product identifier**
- **Trade name:** LHM plus premium
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Hydraulic fluid
- **Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
TRW Automotive Aftermarket
Stratford Road
Shirley
West Midlands
B90 4AX
United Kingdom
Tel. +44.121.506.5000
Fax +44.121.506.5001
www.trwaftermarket.com
cst.uk@trw.com
 - **Informing department:** Tel.: +49 (0) 2631 / 912 - 0
 - **Emergency telephone number:**
Poison Information Center Munich
Phone: +49 (0) 89 - 19 240
Information in German and English

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

R67: Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2013

Version number 2

Revision: 14.11.2013

Trade name: LHM plus premium

(Contd. from page 1)

- **Classification system:**

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

- **Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labelling:**

Distillates (petroleum), hydrotreated middle

- **Hazard statements**

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing mist/vapours/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P331 Do NOT induce vomiting.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:**

Mixture of the substances listed below including additives not requiring identification.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2013

Version number 2

Revision: 14.11.2013

Trade name: LHM plus premium

(Contd. from page 2)

. Dangerous components:

CAS: 64742-46-7 EINECS: 265-148-2	Distillates (petroleum), hydrotreated middle Xn R65 R66-67 Asp. Tox. 1, H304; STOT SE 3, H336	10 - 30%
--------------------------------------	--	----------

. Additional information

For the wording of the listed risk phrases refer to section 16.

4 First aid measures

. Description of first aid measures

- . General information** Instantly remove any clothing soiled by the product.
- . After inhalation** Supply fresh air; consult doctor in case of symptoms.
- . After skin contact**
Wash intensively with water and soap. Use protective skin ointment.
If skin irritation continues, consult a doctor.
- . After eye contact**
Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- . After swallowing**
Do not induce vomiting.
Rinse out mouth.
Instantly call for doctor.
- . Information for doctor**
 - . Most important symptoms and effects, both acute and delayed**
No further relevant information available.
 - . Danger**
In case of ingestion or vomiting product may enter the lung.
Aspiration may cause pulmonary oedema and pneumonitis.
 - . Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- . Extinguishing media**
- . Suitable extinguishing agents**
Extinguishing powder, foam or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- . For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- . Special hazards arising from the substance or mixture**
Inhalation of combustion gases may cause serious health hazards.
During incomplete combustion carbon monoxide can be formed.
- . Advice for firefighters**
 - . Protective equipment:** Wear self-contained breathing apparatus.
- . Additional information**
Remove fill mass from incendiary zone, if possible.
Use water to keep fire exposed containers cool.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2013

Version number 2

Revision: 14.11.2013

Trade name: LHM plus premium

(Contd. from page 3)

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Avoid contact with the product.
Particular danger of slipping on leaked/spilled product.
- **Environmental precautions:**
Prevent from spreading (e.g. by damming-in or oil barriers).
Do not allow to enter drainage system, surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Dispose of the material collected according to regulations.
- **Reference to other sections**
No dangerous materials are released.
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

7 Handling and storage

- **Handling**
- **Precautions for safe handling** Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Do not heat close to flash point.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
 - **Requirements to be met by storerooms and containers:**
Store only in the original container.
Prevent any penetration into the ground.
 - **Information about storage in one common storage facility:**
Store away from oxidizing agents.
 - **Further information about storage conditions:**
Keep container tightly sealed.
Store container in a well ventilated position.
Store under dry conditions.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2013

Version number 2

Revision: 14.11.2013

Trade name: LHM plus premium

(Contd. from page 4)

. PNECs
72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

PNEC oral 9.33 mg/kg food (.)

64742-46-7 Distillates (petroleum), hydrotreated middle

PNEC oral 17000 mg/kg food (.)

. Additional information:

The lists that were valid during the compilation were used as basis.

. Exposure controls
. Personal protective equipment
. General protective and hygienic measures

Avoid close or long term contact with the skin.

Do not carry cleaning cloths impregnated with the product in trouser pockets.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

. Breathing equipment:

Not necessary if room is well-ventilated.

Use a breathing protection if high concentrations are present.

Filter A/P2.

. Protection of hands: Use gloves of stable material (i.e. nitril rubber).
. Material of gloves

Chloroprene rubber, CR

Nitrile rubber, NBR

 Recommended thickness of the material: ≥ 0.2 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

. Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

. Eye protection: Safety glasses recommended during refilling.

9 Physical and chemical properties

. Information on basic physical and chemical properties
. General Information
. Appearance:
. Form:

Fluid

. Colour:

Light green

. Odour:

Mineral-oil-like

. Odour threshold:

Not determined.

. pH-value:

Not determined.

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2013

Version number 2

Revision: 14.11.2013

Trade name: LHM plus premium

(Contd. from page 5)

<ul style="list-style-type: none"> · Change in condition · Melting point/Melting range: < -50 °C (ISO 7308) · Boiling point/Boiling range: 250 - 380 °C (IP 123) 	
· Flash point:	> 110 °C (IP 35)
· Inflammability (solid, gaseous)	Not applicable.
· Ignition temperature:	> 350 °C (ASTM D 286)
· Decomposition temperature:	Thermally in general stable.
· Self-inflammability:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive.
<ul style="list-style-type: none"> · Critical values for explosion: · Lower: 1 Vol % · Upper: 8 Vol % 	
· Vapour pressure at 20 °C:	< 1 hPa
· Density at 20 °C	0.83 g/cm ³
· Evaporation rate	Not determined.
<ul style="list-style-type: none"> · Solubility in / Miscibility with · Water: Insoluble 	
· Partition coefficient (n-octanol/water): > 3 log POW (OECD 117)	
<ul style="list-style-type: none"> · Viscosity: · dynamic: Not determined. · kinematic at 40 °C: 18 mm²/s (ASTM D 445) · Other information No further relevant information available. 	

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Possible formation of peroxide
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Avoid contact with strong oxidizing agents.
- **Hazardous decomposition products:**
None in case of intended use and storage in compliance with instructions.

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2013

Version number 2

Revision: 14.11.2013

Trade name: LHM plus premium

(Contd. from page 6)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 2000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50	2.18 mg/l/4h (rat) (OECD 403)

64742-46-7 Distillates (petroleum), hydrotreated middle

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 2000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50	4.6 mg/l/4h (rat) (OECD 403)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritant effect.

- **Sensitization:** No sensitizing effect known.

- **Additional toxicological information:**

Smallest amounts which can get into the lungs by means of swallowing or subsequent vomiting can cause a pulmonary oedema or pneumonia.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

EC50 (static)	> 10000 mg/l/48h (Daphnia magna) (OECD 202)
LC50 (static)	> 100 mg/l/96h (Pimephales promelas) (OECD 203)

64742-46-7 Distillates (petroleum), hydrotreated middle

EC50	7.38 mg/l/48h (Daphnia magna) (QSAR)
LC50	65 mg/l/96h (Oncorhynchus mykiss) (OECD 203)

- **Persistence and degradability** Heavily biodegradable

- **Other information:** There are no data available about the preparation.

- **Behaviour in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2013

Version number 2

Revision: 14.11.2013

Trade name: LHM plus premium

(Contd. from page 7)

- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation**
Must be specially treated under adherence to official regulations.
The waste code numbers mentioned are recommendations based on the probable use of the product.

- **European waste catalogue**

13 00 00	OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19)
----------	---

13 01 00	waste hydraulic oils
----------	----------------------

13 01 10*	mineral based non-chlorinated hydraulic oils
-----------	--

13 00 00	OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19)
----------	---

13 01 00	waste hydraulic oils
----------	----------------------

13 01 11*	synthetic hydraulic oils
-----------	--------------------------

- **Uncleaned packagings:**
 - **Recommendation:**
Dispose of packaging according to regulations on the disposal of packagings.

14 Transport information

- | | |
|--|-----------------|
| <ul style="list-style-type: none"> · UN-Number <ul style="list-style-type: none"> · ADR, ADN, IMDG, IATA | Void |
| <ul style="list-style-type: none"> · UN proper shipping name <ul style="list-style-type: none"> · ADR, ADN, IMDG, IATA | Void |
| <ul style="list-style-type: none"> · Transport hazard class(es) <ul style="list-style-type: none"> · ADR, ADN, IMDG, IATA · Class | Void |
| <ul style="list-style-type: none"> · Packing group <ul style="list-style-type: none"> · ADR, IMDG, IATA | Void |
| <ul style="list-style-type: none"> · Environmental hazards: <ul style="list-style-type: none"> · Marine pollutant: | No |
| <ul style="list-style-type: none"> · Special precautions for user | Not applicable. |
| <ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2013

Version number 2

Revision: 14.11.2013

Trade name: LHM plus premium

(Contd. from page 8)

. UN "Model Regulation":

-

15 Regulatory information

. Safety, health and environmental regulations/legislation specific for the substance or mixture

. Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

. Hazard pictograms



GHS07 GHS08

. Signal word Danger

. Hazard-determining components of labelling:

Distillates (petroleum), hydrotreated middle

. Hazard statements

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

. Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing mist/vapours/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P331 Do NOT induce vomiting.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

. National regulations

. Information about limitation of use:

Employment restrictions concerning young persons must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning women of child-bearing age must be observed.

. Water hazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 10)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.11.2013

Version number 2

Revision: 14.11.2013

Trade name: LHM plus premium

(Contd. from page 9)

· **Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· **Department issuing data specification sheet:**

This Material Safety Data Sheet has been drawn up in cooperation with:
 DEKRA Consulting GmbH, Hanomagstr. 12, D-30449 Hanover, Germany,
 tel.: (+49) 511 42079 311, reach@dekra.com.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

· *** Data compared to the previous version altered.**

GB